

STYLE P8

**Braided from Ramie fibre with PTFE impregnation
and silicon free run-in lubricant**



Main areas of application:




- Pumps
- Armatures
- Ship service
- Sewage treatment
- Kneading devices
- Stem tubes
- Fittings
- Filters
- Refiners

Characteristics:

- Universal packing for lower temperatures
- Cost effective
- Very robust, shaft protecting HRC45 recommended, packing is protected against rotting
- Excellent at sealing fluids which contains solid substances

Suitable for:

- Paper industry, sewage plants and treatment industries, ship industry and applications in the lower temperature range

			
p [bar]	25 (15*)	100	100
v [m/s]	12	1.5	-
t °C	-50 ... +140 (120*)		
pH	4 - 11		
g/cm ³	1.45		

*practically useful data

Form of delivery:

This packing can be manufactured from 4 to 40 mm square as well as in intermediate, inch sizes and special measurements.

04 - 09 mm	on	1 kg spool	Special length, pre-cut or die formed rings on request.
10 - 15 mm	on	2.5 kg spool	
16 mm and above	on	5 kg spool	

1 kg of packing of the following cross-sections is equivalent to displayed metre lengths:

[size]	04	05	06	1/4"	08	3/8"	10	7/16"	12	1/2"	14	15	16	18	19	20	22	25
[m]	43	27,6	19,2	17,1	10,8	7,6	6,9	5,7	4,79	4,28	3,52	3,07	2,69	2,13	1,91	1,72	1,42	1

All technical information and advice is based on our experience and will be given most conscientiously but without any liability. Indication and figures need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.